



PowerShot S200

Share your creativity with a PowerShot you can take anywhere

Delivering superb performance in any light, with HS System and a bright f/2 lens. The PowerShot S200 puts artistic control into the pockets of photographers who like to shoot creatively and share their images on the move.



PowerShot S200

you can

- Great results in low light, thanks to a bright f/2 lens and HS System with DIGIC 5 processor
- Shoot a variety of subjects with a 24mm ultra-wide angle, 5x zoom lens and 9x ZoomPlus
- Capture detailed images with a 10.1 Megapixel high-sensitivity sensor
- Intelligent IS keeps images sharp and movies steady, even when using full zoom
- Take control with a customisable Lens Control Ring and manual modes
- Connect to smartphones easily with Wi-Fi, and share and backup your images
- Easy viewing with large 7.5 cm (3.0") PureColor II G LCD
- Capture superb images and HD movies in every situation with Smart Auto
- Make a statement with your photos, using Live View Control and Creative Filters

Product Range



PowerShot G16

PowerShot G1 X Mark II
PowerShot G16
PowerShot S120
PowerShot S200



PowerShot S120



PowerShot S200

Canon

f/2
LENS

24mm
WIDE
5x

9x
ZoomPlus

HS
SYSTEM

DIGIC
5

10.1 MEGA
PIXELS
HIGH-SENSITIVITY
CCD

INTELLIGENT
IS

Control Ring

Technical Specifications

PowerShot S200

IMAGE SENSOR	
Type	1/1.7 type high-sensitivity CCD
Effective Pixels	Approx. 10.1 M
Colour Filter Type	Primary Colour
IMAGE PROCESSOR	
Type	DIGIC 5 with iSAPS technology
LENS	
Focal Length	5.2 - 26.0 mm (35 mm equivalent: 24 - 120 mm)
Zoom	Optical 5x ZoomPlus 9x Digital Approx. 4x (with Digital Tele-Converter Approx. 1.4x or 1.8x) ^[1] Combined Approx. 20x
Maximum f/number	f/2.0-f/5.9
Construction	7 elements in 6 groups (1 double-sided aspherical lens, 1 double-sided aspherical UA lens and 1 single-sided aspherical lens)
Image Stabilization	YES - lens shift-type, approx. 3-stop ^[2] Intelligent IS
FOCUSING	
Type	TTL
AF System / Points	AiAF (9-point or Face Detection with Face Select and Track), 1-point AF (any position is available or fixed centre)
AF Modes	Single, Continuous, Servo AF/AE ^[3] , Tracking AF
AF Point Selection	Size (Normal, Small)
AF Lock	YES
AF Assist Beam	YES
Manual Focus	YES
Closest Focusing Distance	3 cm (W) from front of lens in macro
EXPOSURE CONTROL	
Metering Modes	Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (centre or linked to Face Detection AF or FlexiZone AF frame)
AE Lock	YES
Exposure Compensation	+/- 2 EV in 1/3 stop increments. Enhanced i-Contrast for automatic dynamic range correction
ISO Sensitivity	AUTO, 80, 100, 200, 400, 800, 1600, 3200, 6400
SHUTTER	
Speed	1 - 1/2000 sec. (factory default) 15 - 1/2000 sec. (total range - varies by shooting mode)
WHITE BALANCE	
Type	TTL
Settings	Auto (including Face Detection WB), Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
COLOUR MATRIX	
Type	sRGB
LCD MONITOR	
Monitor	7.5 cm (3.0") PureColor II G LCD (TFT) Approx. 461,000 dots
Coverage	Approx. 100%
Brightness	Adjustable to one of five levels. Quick-bright LCD

FLASH	
Modes	Auto, Manual Flash On / Off, Slow Synchro
Slow Sync Speed	YES - fastest speed 1/2000 sec.
Red-Eye Reduction	YES
Flash Exposure Compensation	+/- 2 EV in 1/3 stop increments. Face Detection FE, Safety FE, Smart Flash Exposure
Flash Exposure Lock	YES
Manual Power Adjustment	3 levels with internal flash
Second Curtain Synchronisation	YES
Built-in Flash Range	50 cm - 7.0 m (W) / 50 cm - 2.3 m (T)
External Flash	Canon High Power Flash HF-DC2
SHOOTING	
Modes	Smart Auto (36 scenes detected), Program AE, Shutter priority AE, Aperture priority AE, Manual, Live View Control, SCN (Portrait, Smooth Skin, Smart Shutter (Smile, Wink Self-Timer, FaceSelf-Timer), High-speed Burst (2.5 MP), Stitch Assist, Snow, Fireworks), Creative Filters (Fish-eye Effect, Miniature Effect, Toy Camera Effect, Soft Focus, Monochrome, Super Vivid, Poster Effect, Color Accent, Color Swap)
Modes In Movie	Smart Auto (21 scenes detected), Program AE, Portrait, Miniature Effect, Monochrome, Super Vivid, Poster Effect, Snow, Fireworks, Color Accent, Color Swap
Photo Effects	My Colors (My Colors Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)
Drive Modes	Single, Continuous, Continuous with AF, Self-Timer
Continuous Shooting	Approx. 1.9 shots/sec High-speed Burst (2.5MP): 4.5 shots/sec With AF: Approx. 0.8 shots/sec With Live View: Approx. 0.8 shots/sec (all speeds are until memory card becomes full) ^{[4][5]}
RECORDING PIXELS / COMPRESSION	
Image Size	4:3 - (L) 3648 x 2736, (M1) 2816 x 2112, (M2) 1600 x 1200, (S) 640 x 480 16:9 - (L) 3648 x 2048, (M1) 2816 x 1584, (M2) 1920 x 1080, (S) 640 x 360 3:2 - (L) 3648 x 2432, (M1) 2816 x 1880, (M2) 1600 x 1064, (S) 640 x 424 1:1 - (L) 2736 x 2736, (M1) 2112 x 2112, (M2) 1200 x 1200, (S) 480 x 480 Resize in playback (M2, S)
Compression	Superfine, Fine
Movies	(HD) 1280 x 720, 24 fps, (L) 640 x 480, 30 fps Miniature Effect (HD) 4.8 fps, 2.4 fps, 1.2 fps, (L) 6fps, 3 fps, 1.5 fps
Movie Length	(HD) Up to 4 GB or 29 min. 59 sec. ^[6] (L and M) Up to 4 GB or 1 hour ^[5]
FILE TYPES	
Still Image Type	JPEG compression, (Exif 2.3 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
Movies	MOV [Video: H.264. Audio: Linear PCM (stereo)]
DIRECT PRINT	
Canon Printers	Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge
PictBridge	YES (via USB or Wireless LAN)

Technical Specifications

PowerShot S200

OTHER FEATURES	
GPS	GPS via mobile (linked to compatible smartphone)
Red-Eye Correction	YES – during shooting and playback
Intelligent Orientation Sensor	YES
Histogram	YES
Playback Zoom	Approx. 2x – 10x
Self Timer	Approx. 2 or 10 sec., Custom
Menu Languages	English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese
INTERFACE	
Computer	Hi-Speed USB (MTP, PTP) dedicated connector (Mini-B compatible)
Other	HDMI Mini Connector (HDMI-CEC compatible) A/V output (PAL/NTSC)
Computer / Other	Wi-Fi (IEEE802.11 b/g/n), (2.4 GHz only) ^[7]
MEMORY CARD	
Type	SD, SDHC, SDXC
SUPPORTED OPERATING SYSTEM	
PC & Macintosh	Windows 8 / 7 SP1 / Vista SP2/ XP SP3 Mac OS X v10.6 – 10.9 For Wireless LAN connection to a PC: Windows 8 / 7 SP1 Mac OS X v10.6.8 / 10.7 / 10.8.2 or later
SOFTWARE	
Browsing & Printing	ImageBrowser EX
Other	CameraWindow, PhotoStitch, Map Utility

POWER SOURCE	
Batteries	Rechargeable Li-ion Battery NB-6LH (battery and charger supplied)
Battery Life	Approx. 200 shots Eco mode approx. 300 shots Approx. 300 min. playback
A/C Power Supply	Optional, AC Adapter Kit ACK-DC40
ACCESSORIES	
Cases / Straps	Soft Case DCC-1450 Soft Case DCC-1920 Travel Case DCC-2500
Flash	Canon High Power Flash HF-DC2
Power Supply & Battery Chargers	Battery Pack NB-6L Battery Pack NB-6LH Battery Charger CB-2LYE AC Adapter Kit ACK-DC40
Other	HDMI Cable HTC-100 Interface cable IFC-400PCU
PHYSICAL SPECIFICATIONS	
Operating Environment	0 – 40 °C, 10 – 90% humidity
Dimensions (W x H x D)	99.8 x 59.0 x 26.3 mm
Weight	Approx. 181 g (including battery and memory card)

All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated.

Subject to change without notice.

[1] Depending on the image size selected.

[2] Values at maximum optical focal length. Cameras whose focal length exceeds 350 mm (35 mm equivalent) are measured at 350 mm.

[3] Some settings limit availability.

[4] Under conditions where the flash does not fire.

[5] Depending on memory card speed / capacity / compression setting.

[6] The following Speed Class memory cards are required for maximum record time: (HD) 1280 x 720 Speed Class 4 or above. (Full HD) 1920 x 1080 Speed Class 6 or above. (iFrame) 1280 x 720 Speed Class 6 or above.

[7] Wi-Fi use may be restricted in certain countries or regions. Wi-Fi support varies by device and region.

For more information visit www.canon-europe.com/wirelesscompacts

Share your creativity with a PowerShot you can take anywhere

PowerShot S200



Delivering superb performance in any light, with HS System and a bright f/2 lens. The PowerShot S200 puts artistic control into the pockets of photographers who like to shoot creatively and share their images on the move.

Sales start date: May 2014

Positioning: A pocketable camera for the creative photographer on the move

Product Details:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PowerShot S200 BLACK	8408B015	8714574615875	CHF 358.00
PowerShot S200 WHITE	8675B015	8714574615912	CHF 358.00

Optional Accessories:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
AC Adapter Kit ACK-DC40	2610B003	4960999571706	CHF 118.00
Battery Charger CB-2LYE	2609B001	4960999571676	CHF 98.00
Battery Pack NB-6LH	8724B001	496099989952	CHF 68.00
High Power Flash HF-DC2	5189B001	4960999782232	CHF 168.00
Interface Cable IFC-400PCU	9370A001	4960999209906	CHF 38.00
AV Stereo Cable AVC-DC400ST	4076B001	4960999659275	CHF 28.00
HDMI Cable HTC-100	2384B001	4960999530383	CHF 88.00
Soft Case DCC-1450	0033X729	8714574558738	CHF 38.00
Soft Case DCC-1920	0038X888	8714574610337	CHF 68.00
Travel Case DCC-2500	0038X887	8714574610320	CHF 48.00

Logistics Information:

Pack Description	Qty	Dimensions (L x W x H in mm)	Weight (Net / Gross in kg)
Each	1	159 x 138 x 61	0.304 / 0.397
Carton	15	447 x 326 x 202	5.955 / 6.749
Euro Pallet	375	1200 x 800 x 1160	- / 174.0

Euro Pallet Information:

Layers	
Layers per Pallet	5
Cartons per Layer	5
Products per Layer	75

What's in the box?

- PowerShot S200
- Wrist Strap WS-DC11
- Battery Pack NB-6LH
- Battery Charger CB-2LYE
- AC Cable
- User Manual Kit