

PowerShot SX60 HS



Explore detail at a distance

Zoom into the exquisite detail of distant wildlife. Capture stunning ultra-wide landscapes with this hugely versatile and gifted 65x Wi-Fi bridge camera, which combines fun with expert control.



- Zoom in 65x on faraway detail or capture stunning ultra-wide landscapes
- Easily keep your subject in the frame with Zoom Framing Assist
- Shoot stunning images in any light with Intelligent IS and HS System
- Capture all the action with fast response and sustained continuous shooting
- Create brilliant photos with ultimate ease using Hybrid Auto and enjoy a fun movie summary of your day
- Connect with ease using Wi-Fi with NFC and enjoy remote shooting via smartphone
- Shoot smooth Full HD 60p movies with expert control using Manual Movie Mode
- Explore the world of Full Manual and RAW
- Enjoy comfortable, steady shooting thanks to ergonomic design and Electronic Viewfinder
- Play with your creativity and unlock your inner artist

Product Range



PowerShot SX60 HS



PowerShot SX520HS



PowerShot SX510 HS

PowerShot SX60 HS

PowerShot SX520 HS
PowerShot SX510 HS
PowerShot SX400 IS

Technical Specifications

IMAGE SENSOR

Type
Effective Pixels
Effective / Total Pixels
Colour Filter Type

1/2.3 type back-illuminated CMOS
 Approx. 16.1M ^[14]
 Approx. 16.8M
 Primary Colour

IMAGE PROCESSOR

Type
 DIGIC 6 with iAPDS technology

LENS

Focal Length
Zoom

3.8 – 247.0 mm (35 mm equivalent: 21 – 1365 mm)
 Optical 65x
 ZoomPlus 130x
 Digital Approx. 4x (with Digital Tele-Converter approx. 1.6x or 2.0x ^[1]).
 Combined approx. 260x
 f/3.4-f/6.5

Maximum f/number
Construction

15 elements in 11 groups (1 double sided aspherical lens and 3 UD lenses)

Image Stabilisation

Yes (lens shift-type), approx. 3.5-stop ^[13], Intelligent IS with 5-axis Enhanced Dynamic IS

Ultrasonic Motor (USM)

Yes

FOCUSING

Type
AF System/ Points

TTL
 Face Detect, 1-point AF (any position, fixed to centre or Face Select and Track)

AF Modes
AF Point Selection

Single, Continuous, Servo AF/AE ^[6], Tracking AF
 Manual selection using FlexiZone AF/AE, Size (Normal, Small)

AF Lock
AF Assist Beam
Manual Focus
Focus Bracketing
Closest Focusing Distance

Yes, via customisable buttons
 Yes
 Yes, plus MF Peaking
 Yes
 0 cm (W) from front of lens in Macro

EXPOSURE CONTROL

Metering modes

Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (centre or linked to Face Detection AF or FlexiZone AF frame)

AE Lock
Exposure Compensation

Yes, via customisable buttons
 +/- 3 EV in 1/3 stop increments
 Manual and automatic dynamic range correction
 Automatic shadow correction

AEB
ISO sensitivity

1/3 – 2 EV in 1/3 stop increments
 100, 125, 160, 200, 250, 320, 400, 500, 640, 800, 1000, 1250, 1600, 2000, 2500, 3200
 AUTO ISO: 100 – 3200 (possible to set Max. ISO speed and rate of change)

SHUTTER

Speed

1 – 1/2000 sec. (factory default)
 15 – 1/2000 sec. (total range – varies by shooting mode)

WHITE BALANCE

Type
Settings

TTL
 Auto (including Face Detection WB), Daylight, Shade, Cloudy, Tungsten, Fluorescent, Fluorescent H, Flash, Custom 1, Custom 2
 Multi-area WB correction available in Smart Auto
 White Balance Compensation
 sRGB

Type

VIEWFINDER

Viewfinder
Viewfinder / Coverage
Dioptr Correction

EVF (0.17 type), 4:3 aspect ratio, approx. 922,000 dots
 Approx. 100%
 Yes

LCD MONITOR

Monitor

Vari-angle 7.5 cm (3.0") PureColor II VA (TFT), Approx. 922,000 dots
 Approx. 100%
 Adjustable to one of five levels. Quick-bright LCD

Coverage
Brightness

FLASH

Modes
Slow Sync Speed

Auto, Manual Flash On / Off, Slow Synchro
 Yes.
 Fastest speed:
 1/2000 sec. (built-in flash)
 1/250 sec. (external flash)
 1/2000 sec. (external flash using high-speed synchro)

Red-Eye Reduction
Flash Exposure Compensation
Flash Exposure Lock

Yes
 +/- 2 EV in 1/3 stop increments. Face Detection FE, Safety FE, Smart Flash Exposure
 Yes, via customisable buttons

Manual Power Adjustment

3 levels with internal flash (up to 19 levels with external EX Speedlite 270EX II, 320EX and 430EX II, 22 levels with 580EX II, 600EX and 600EX-RT ^[2])
 Yes

Second Curtain Synchronisation
Built-in Flash Range
External Flash

50 cm – 5.5 m (W) / 1.8 m – 3.0 m (T)
 E-TTL with EX Speedlite range ^[2]

SHOOTING

Modes

Smart Auto (58 scenes detected), Program AE, Shutter priority AE, Aperture priority AE, Manual, Custom 1, Custom 2, Hybrid Auto, Creative Shot, Sports, SCN (Portrait, Smart Shutter (Smile, Wink Self-Timer, FaceSelf-Timer), Handheld Night Scene, Low Light (4.0MP), Snow, Fireworks), Creative Filters (High Dynamic Range, Fish-eye Effect, Miniature Effect, Toy Camera Effect, Soft Focus, Monochrome, Super Vivid, Poster Effect), Movie

Modes in Movie

Smart Auto (21 scenes detected), Standard, Program AE, Manual, Portrait, Miniature Effect, Monochrome, Super Vivid, Poster Effect, Snow, Fireworks, iFrame Movie, Super Slow Motion Movie

Photo Effects

My Colors (My Colors Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)

Drive modes

Single, Auto Drive, Continuous, Continuous with AF, Self-Timer

Continuous Shooting

Approx. 6.4 shots/sec until memory card becomes full ^[12] with AF; Approx. 3.8 shots/sec ^{[3][4]} with Live View; Approx. 4.6 shots/sec ^{[3][4]}

RECORDING PIXELS / COMPRESSION

Image Size

4:3 - (RAW, L) 4608 x 3456, (M1) 3264 x 2448, (M2) 2048 x 1536, (S) 640 x 480
 16:9 - (RAW, L) 4608 x 2592, (M1) 3264 x 1832, (M2) 1920 x 1080, (S) 640 x 360
 3:2 - (RAW, L) 4608 x 3072, (M1) 3264 x 2176, (M2) 2048 x 1368, (S) 640 x 424
 1:1 - (RAW, L) 3456 x 3456, (M1) 2448 x 2448, (M2) 1536 x 1536, (S) 480 x 480
 4:5 - (RAW, L) 2768 x 3456, (M1) 1952 x 2448, (M2) 1232 x 1536, (S) 384 x 480
 Resize in playback (M2, S)

Compression
Movies

RAW, Superfine, Fine (Full HD) 1920 x 1080, 60 fps / 30 fps (HD) 1280 x 720, 30 fps (L) 640 x 480, 30 fps
 Super Slow Motion Movie (L) 640 x 480, 120 fps, (M) 320 x 240, 240 fps
 Miniature Effect (HD, L) 6 fps, 3 fps, 1.5 fps
 Hybrid Auto (HD) 30 fps
 iFrame Movie (Full HD) 30 fps (Full HD & HD) Up to 4 GB or 29 min. 59 sec. ^[7] (L and M) Up to 4 GB or 1 hour ^[4] (Super Slow Motion Movie) Approx. 30 sec.

Movie Length

FILE TYPES

Still Image Type

JPEG compression (Exif 2.3 [Exif Print] compliant) / Design rule for Camera File system and DPOF ver. 1.1 compliant), RAW, RAW+JPEG

Movies

MP4 [Video: MPEG-4 AVC / H.264, Audio: MPEG-4 AAC-LC (stereo) recording level can be manually adjusted by user] iFrame

DIRECT PRINT

Canon Printers

Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge
 Yes (via USB or Wireless LAN)

PictBridge

OTHER FEATURES

GPS

Red-Eye Correction
My Camera / My Menu
My Category
Intelligent Orientation
Sensor
Histogram
Playback zoom
Self Timer
Menu Languages

GPS via mobile (linked to a compatible smartphone)
 Yes, during shooting and playback
 My Menu customisation available
 Image tagging feature
 Yes

Yes, live histogram
 Approx. 2x – 10x
 Approx. 2 or 10 sec., Custom
 English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese, Hebrew

PowerShot SX60 HS

Technical Specifications

INTERFACE

Computer

Hi-Speed USB (MTP, PTP) DIGITAL connector
HDMI Mini Connector

Other

A/V output (PAL/NTSC)
External microphone (3.5 mm Stereo mini jack)
Wireless LAN (IEEE802.11b/g/n), (2.4 GHz only), with NFC support ^[1]

Computer/Other

MEMORY CARD

Type

SD, SDHC, SDXC (UHS Speed Class 1 compatible)

SUPPORTED OPERATING SYSTEM

PC & Macintosh

Windows 8 / 8.1 / 7 SP1
Mac OS X 10.8 / 10.9
For Wi-Fi connection to a PC:
Windows 8 / 8.1 / 7 SP1
Mac OS X 10.8.2 or later / 10.9

SOFTWARE

Browsing & Printing Other

ImageBrowser EX
CameraWindow
PhotoStitch
Map Utility
Digital Photo Professional for RAW development

Image Manipulation

POWER SOURCE

Batteries

Rechargeable Li-ion Battery NB-10L (battery and charger supplied)

Battery life

Approx. 340 shots
Eco mode approx. 450 shots

A/C Power Supply

Approx. 360 min. playback
Optional, AC Adapter Kit ACK-DC80

ACCESSORIES

Cases / Straps

Soft Case DCC-850
PowerShot Neck Strap NS-100
PowerShot Accessory Organizer
Lens Hood LH-DC90

Lenses

Filter Adapter FA-DC67A (Compatible with Canon 67mm
Filters: Circular Polarizing PL-C B, Protect Filter, ND Filter)

Flash

Canon Speedlite (including 270EX, 270EX II, 320EX, 430EX II, 580EX II, 600EX, 600EX-RT ^[2])
Speedlite Transmitter ST-E2, Speedlite bracket SB-E2, Off-Camera Shoe Cord OC-E3
Remote Switch RS-60E3
AC Adapter Kit ACK-DC80, Battery Charger CB-2LCE

Remote Controller / Switch Power Supply & Battery Chargers Other

Interface cable IFC-400PCU
Canon AV cable AVC-DC400ST
Canon HDMI Cable HTC-100

PHYSICAL SPECIFICATIONS

Operating Environment

0 – 40 °C, 10 – 90% humidity
127.6 x 92.6 x 114.3 mm

Dimensions (W x H x D)

Approx. 650 g (including battery and memory card)

Weight

All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated.
Subject to change without notice.

[1] Depending on the image size selected.

[2] Not all functions of the flash are supported.

[3] Under conditions where the flash does not fire.

[4] Depending on memory card speed / capacity / compression setting.

[6] Some settings limit availability.

[7] The following Speed Class memory cards are required for maximum record time: (HD) 1280 x 720 Speed Class 4 or above, (Full HD) 1920 x 1080 Speed Class 6 or above, (iFrame) 1280 x 720 Speed Class 6 or above.

[11] Wi-Fi use may be restricted in certain countries or regions. Wi-Fi support varies by device and region. For more information visit www.canon-europe.com/wirelesscompact

[12] Sustained continuous shooting function requires compatible SDHC/SDXC UHS Speed Class 1 memory card, total number of frames captured varies depending on shooting subject.

[13] Values at maximum optical focal length. Cameras whose focal length exceeds 350 mm (35 mm equivalent) are measured at 350 mm.

[14] Image processing may cause a decrease in the number of pixels.

PowerShot SX60 HS

Explore detail at a distance

Zoom into the exquisite detail of distant wildlife. Capture stunning ultra-wide landscapes with this hugely versatile and gifted 65x Wi-Fi bridge camera, which combines fun with expert control.



Sales Start Date: October 2014

Product Details:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
Digital Camera PowerShot SX60 HS EU23	9543B002AA	4549292017380	<Please fill in RRP>

Optional Accessories:

Product Name	Mercury Code	EAN Code	Recommended Retail Price
Battery Charger CB-2LCE	5670B001AA	4960999796130	<Please fill in RRP>
Battery Pack NB-10L	5668B001AA	4960999796093	<Please fill in RRP>
AC Adapter Kit ACK-DC80	5667B003AA	4960999795935	<Please fill in RRP>
Lens Hood LH-DC90	9843B001AA	4549292017755	<Please fill in RRP>
Filter Adapter FA-DC67A	4728B001AA	4960999677187	<Please fill in RRP>
Lens Filter Protect 67 mm	2598A001AA	4960999430973	<Please fill in RRP>
Circular Polarizing PL-C B Filter 67 mm	2189B001AA	4960999455778	<Please fill in RRP>
Speedlite 600EX EUR	5739B003AA	4960999810195	<Please fill in RRP>
Speedlite 270EX II EUR	5247B003AA	4960999783246	<Please fill in RRP>
Speedlite 320EX EUR	5246B003AA	4960999786032	<Please fill in RRP>
Speedlite 430EX II EUR	2805B003AA	4960999617947	<Please fill in RRP>
Speedlite Transmitter ST-E2	2478A004AA	4960999581538	<Please fill in RRP>
Camera Remote Switch RS60-E3	2469A002AA	4960999581354	<Please fill in RRP>
Off Camera Shoe Cord OC-E3	1950B001AA	4960999417271	<Please fill in RRP>
Speedlite Bracket SB-E2	1949B001AA	4960999417264	<Please fill in RRP>
Speedlite 580EX II	1946B003AA	4960999417165	<Please fill in RRP>
Interface cable IFC-400PCU	9370A001AA	4960999209906	<Please fill in RRP>
AV Cable AVC-DC400ST	4076B001AA	4960999659275	<Please fill in RRP>
HDMI Cable HTC-100	2384B001AA	4960999530383	<Please fill in RRP>
Soft Case DCC-850	1872V639	8714574560380	<Please fill in RRP>
PowerShot Accessory Organizer	0036X433	8714574583167	<Please fill in RRP>
PowerShot Neck Strap NS-100	0039X579	8714574617268	<Please fill in RRP>

Canon

PowerShot SX60 HS

Explore detail at a distance

Zoom into the exquisite detail of distant wildlife. Capture stunning ultra-wide landscapes with this hugely versatile and gifted 65x Wi-Fi bridge camera, which combines fun with expert control.



Measurement / Logistic Information:

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (mm)	Width (mm)	Height (mm)	Net Weight (kg)	Gross Weight (kg)
Digital Camera PowerShot SX60 HS EU23	9543B002AA	EA	Each	1	191.5	147.5	127	0.825	1.168
		CT	Carton	6	411	315	230	7.01	7.63
		EP	Euro Pallet	150	1200	800	1210	N/A	109
Euro Pallet Information			Layers per pallet	5					
			Cartons per layer	5					
			Products per layer	30					

What's in the box?

- PowerShot SX60 HS
- Lens Cap (with strap)
- Neck Strap NS-DC11
- Battery Pack NB-10L
- Battery Charger CB-2LCE
- AC Cable
- User Manual Kit