# **MULTIFUNCTION PRINTER OFFERING** SPEED, SIMPLICITY, AND SECURITY.

The i-SENSYS MF520 series are black and white multi-function, high-volume printers. They are aimed at small businesses and teams in larger enterprises requiring high-quality, fast printing with mobile connectivity.







MF525x

MF525x

- Save time with fast print speeds of up to 43ppm
- Increase productivity with double sided, single pass scanning
- High quality 1200 x 1200 dpi print resolution
- · Easy operation with large colour touch screen
- Improved flexibility with varied media support; A4, A5, A6
- Increase control with the Universal Login Manager
- · Enhanced security & accounting with uniFLOW
- Easy mobile integration with QR code & NFC function
- Improve quality & reliability with Canon Genuine all-in-one cartridges
- Customise your workflow with the Application Library

### **OPTIONAL ACCESSORIES**

#### Paper feeder PF-C1

• Additional 550 sheet paper cassette, 3 units can be added to main unit.

#### Barcode Print Kit- E1E (Available on both)

 Installs bar code fonts for bar code printing. This kit, which is delivered electronically, includes a license access certificate for activation.

#### Send PDF Security Feature Set-E1 (Available on both)

• Send encrypted PDF and add digital device signature to PDF files. This kit, which is delivered electronically, includes a license access certificate for activation.

### Telephone 6 Kit Long Cord (Available on MF525x)

· Optional telephone handset for fax function.

### **TECHNICAL SPECIFICATIONS**

Machine type Available functions

Mono Laser All-In-One MF522x: Print, Copy and Scan MF525x: Print, Copy, Scan and Fax

PRINTER Print speed

Single sided : Up to 43 ppm (A4) Up to 65.2 ppm(A5-Landscape)

Double sided: Up to 34.4 ipm (A4) Printing method Monochrome laser beam printing Up to 1200 x 1200 dpi Print quality Print resolution 600 x 600 dpi

Warm-up time Approx. 14 seconds or less from power on

First Print Out Time Approx: 6.2 seconds or less

Printer languages UFRII, PCL 5e1, PCL6, Adobe® PostScript

93 PCL fonts 136 PostScript fonts Fonts

5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)

Toner saver mode Yes

Advanced printing features

Secure Print
Print from USB memory key (JPEG/TIFF/PDF)
Barcode Print<sup>2</sup>
Touch & Print (NFC)(MF525x only)
Google Cloud Print Ready
IOS: AirPrint, Canon PRINT Business app
Android; Mopria certified, Canon PRINT Business app

Single sided (A4): Up to 43 ppm Double sided (A4): Up to 34.4 ipm

Frame Frase, Collate, 2 on 1, 4 on 1, ID card copy

COPIER

First Copy Output Time (FCOT)

ADF (A4): Approx. 6.4 seconds or less Platen (A4): Approx. 6.3 seconds or less Up to 600 x 600 dpi

Copy resolution Text, Text/Photo (Default), Text/Photo (High Quality), Photo

Copy modes Double sided copying 2-sided to 2-sided (Automatic)

Multiple copy

Reduction / Enlargement

Other features

SCANNER

Scan resolution

Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi Scan speed

Up to 999 copies

25-400% in 1% increments

Single sided mono: 38ipm (300x600dpi) Single sided colour: 13ipm (300x600dpi) Double sided mono: 70ipm (300x600dpi) Double sided colour: 26ipm (300x600dpi)

24 bit/24 bit (input/output) Colour scanning depth Grevscales 256 levels

TWAIN, WIA, ICA Compatibility Max. scan width 216mm

Scan to E-mail / PC / USB memory key / FTP TIFF/JPEG/PDF/Compact PDF/Searchable PDF/Encrypted PDF $^3$ /PDF (Digital signature) $^3$ 

Scan to Cloud TIFF/JPEG/PDF/PNG4

ITU-T.37

FAX MF525x only

Modem speed 33.6 Kbps (Up to 3 seconds/page<sup>5</sup>) Receive mode

Fax only, Fax/Tel Auto Switch, Answer Mode, Manual

Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi Fax resolution

FAX memory Up to 512 pages<sup>5</sup> Speed dials Up to 281 dials

Max. 299 dials / Max. 299 destinations Group dials/destinations

Sequential broadcast Max. 310 destinations

Permanent fax memory backup (Backup with flash Memory backup

50-sheet ADF

250-sheet

Double sided faxing Yes (Transmit and Receive)

Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports Other features

Platen, 2-sided ADF (single pass)

550-sheet cassette 100-sheet multi-purpose tray

550-sheet cassette x 3

MEDIA HANDLING

Scanner type Paper input (Standard)

Paper input (Option)

Paper output Media types

Media weights

Double sided printing

**INTERFACE & SOFTWARE** 

Interface type

Operating System compatibility

Network Protocol

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

Windows\* 10 / Windows\* 8.1 / Windows\* 7 / Server\* 2016 / Server\* 2012R2 / Server\* 2012 / Server\* 2008R2 / Server\* 2008 Mac OS X version 10.8.5 & up Linux\*

Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope Cassette (Standard and optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, GLTR, GLGL, Foolscap, 16K, Custom sizes: Min. 105 x 148 mm Max. 215.9 x 355.6 mm.

Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Postcard, Indexcard, Envelope (COMIO, Monarch, CS, DL), Custom sizes: Min 76.2 x 127 mm Max. 215.9 x 355.6 mm.

ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 105 x 128 mm Max 215.9 x 355.6 mm

A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, Foolscap Custom size - Min. 210 x 279.4 mm Max. 215.9 x 355.6 mm 60 to 120 g/m²

Cassette (standard and optional): 52 to 120 g/m² multi-purpose tray: 52 to 199 g/m² ADF: 50 to 105 g/m²

Print; LPD, RAW, Port9100, IPP, IPPS, WSD (IPv4,IPv6)

Scan; Email, SMB, WSD-Scan(IPv4, IPv6), FTP-Scan, iFAX

TCP/IP Application Services: Bonjour(mDNS), HTTP, HTTPS, POP before SMTP (IPv4,IPv6) DHCP, ARP+PING, Auto IP, WINS (IPv4) DHCPv46 (IPv6)

Management: SNMPv1, SNMPv3 (IPv4,IPv6)

Security (wired): IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS)

Security (wireless): WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(AES)



### **TECHNICAL SPECIFICATIONS**

### i-SENSYS MF522x \ MF525x

Software and printer management

MF Scan Utility,
Remote User Interface (RUI),
Department ID Management,
Toner Status Tool,
IW Management Console: Server-based software for
centralised management of a fleet of devices
eMaintenance: embedded RDS allows remote eMaintenance
services Such as meter capture, automatic consumables
management and remote diagnostics.
Universal Log-in Manager
uniFLOW online Express
uniFLOW compatibility with embedded uniFLOW Login
Device Client

GENERAL FEATURES

Recommended Monthly Print Volume

Duty cycle Processor Speed Memory

Control panel

Dimensions with trays (W x D x H)

Installation space (W x D x H) Weight

Operating environment

**Power Source Power Consumption**  2,000 - 7,500 pages per month

Max. 150,000 pages per month

800MHz x 2

1GB

12.7 cm LCD Colour Touch Screen MF525x: 494 mm x 464 mm x 452 mm MF522x: 480 mm x 464 mm x 452 mm

741 mm x 1.105 mm x 1.214 mm

Approx. 20.0 Kg

Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)

220-240V(±10%) 50/60Hz (±2Hz)

Maximum: Approx. 1,380 W Standby: Approx. 17 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.5 kWh/week (230V)

please go to: http://www.canon-europe.com/For Work/Lot26/index.aspx

Noise Levels

Consumables

Cartridges

Sound Pressure<sup>8</sup>: Active: 53 dB Standby: 28 dB Sound Power<sup>8</sup>: Active: 72.9 dB<sup>9</sup> Standby: Inaudible

Cartridge 041 (10,000 pages <sup>10</sup>)<sup>11</sup> Cartridge 041H (20,000 pages <sup>10</sup>)<sup>11</sup>

Paper Feeder PF-CI (550-sheet cassette)
TEL 6 Kit Long Cord (Telephone handset)(MF525x only)
Barcode Printing Kit-EIE
MiCard Multi (Card reader for identification with RFID or
magnetic cards with uniFLOW)
Micard Plus (Card reader for identification with RFID or
magnetic cards with uniFLOW)
MiCard Attachment Kit-BI

Send PDF Security Feature Set-E1 Plain Pedestal-V1

Notes:

<sup>10</sup> A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

<sup>10</sup> A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

<sup>10</sup> Accessory - Barcode Printing Kit-EIE - is required.

<sup>10</sup> Accessory - Send PDF Security Feature Set-EI is required.

<sup>10</sup> Sean by MF Scan Utility or Canon PRINT Business app.

<sup>10</sup> Based on ITU-T Standard Chart No. 1

<sup>10</sup> Linux support both printing and scanning.

Available from December 2018.

<sup>10</sup> Duty cycle is defined as the maximum number of printed pages for a single peak month.

Any usage above the recommended duty cycle may decrease the life of the product.

<sup>10</sup> Declared noise emission in accordance with 150 9296.

<sup>10</sup> Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779.

<sup>10</sup> Based on ISO/IEC 19752.

<sup>10</sup> Printer ships with Cartridge 041 (10,000 pages).

**English** edition © Canon Europa N.V.,2018



Canon Inc. canon.com Canon Europe canon-europe.com

### MULTIFUNCTION PRINTER OFFERING SPEED, SIMPLICITY, AND SECURITY.

The i-SENSYS MF520 series are black and white multi-function, high-volume printers. They are aimed at small businesses and teams in larger enterprises requiring high-quality, fast printing with mobile connectivity.

Sales Start Date: April 2018

## i-SENSYS MF522x $\setminus$ MF525x



### PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
i-SENSYS MF522x	2223C004AA	4549292090307
i-SENSYS MF525x	2223C003AA	4549292090291

#### ACCESSORIES:

Product Name	Mercury Code	EAN Code
Paper Feeder PF-C1	0865C001AA	4549292050691
MiCard Attachment kit-B1	5146B002AA	4549292027235
Barcode Printing Kit-E1E	5143B002AA	N/A (e-delivery)
Send PDF Security Feature Set-E1	9594B002AA	N/A (e-delivery)
Telephone 6 Kit EU (CW)	0752A054AA	4960999453910
Telephone 6 Kit UK (CW)	0752A053AA	4960999453897
Telephone 6 Kit SA (CW)	0752A055AA	4960999453927
Plain Pedestal-V1	2223C022AA	8714574655673

### CONSUMABLES:

Product Name	Mercury Code	EAN Code
Cartridge 041	0452C002AA	4549292072495
Cartridge 041H	0453C002AA	4549292072525

### EASY SERVICE PLAN:

Product Name	Mercury Code	EAN Code
Installation service	7950A546AA	4960999794426
3-year on site next day service - Pack D	7950AA68AA	8714574644608

