
A SMART AND SECURE MULTIFUNCTION MONO PRINTER, DESIGNED TO FIT SEAMLESSLY INTO ANY SMALL AND HOME OFFICE ENVIRONMENTS

Compact black & white multifunctional printer delivering impressive efficiency and up-to date security technology features

i-SENSYS MF287dw





TECHNICAL Specifications

i-SENSYS MF287dw

c	ENERAL SPECIFICATIONS		
Machine Type	Mono Laser All-In-One		
Available Functions	Print, Copy, Scan and Fax		
	PRINT SPECIFICATIONS		
Print Speed	Single sided: Up to 33.2 ppm (A4) Double sided: Up to 20.9 ipm (A4)		
Printing Method	Monochrome laser beam printing		
Print Resolution	Up to 1200 x 1200 dpi		
Warm-up Time	Approx. 15 seconds or less from power on		
First-Print-Out Time	Approx: 5.0 seconds or less		
Printer Languages	UFRII-LT, PCL 5e ¹ , PCL6		
Fonts	45 PCL fonts		
Print Margins	5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)		
Toner Saver Mode	Yes		
Advanced Printing Features	iOS: AirPrint, Canon PRINT app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT app Microsoft Universal Print support		
	COPY SPECIFICATIONS		
Copy Speed	Single sided: Up to 33.2 ppm (A4) Double sided: Up to 20.9 ipm (A4)		
First-Copy-Out Time	ADF (A4): Approx. 8.6 seconds or less Platen (A4): Approx. 7.3 seconds or less		
Copy Resolution	Up to 600 x 600 dpi		
Copy Modes	Text/Photo, Text/Photo (High speed), Photo, Text		
Double Sided Copying	1-sided to 2-sided (Automatic)		
Multiple Copies	Up to 999 copies		
Reduction / Enlargement	25-400% in 1% increments		
Other Features	Collate Copies, 2 on 1, 4 on 1, ID card copy, Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Two-sided Original, Sort, N on 1, Sharpness, Erase Frame, Copy ID Card		
	SCAN SPECIFICATIONS		
Standard Type	Colour		
Scan Resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi		
Scan Speed	Platen: Single sided mono: 2.7 sec/page (300x600dpi) Single sided colour: 3.5 sec/page (300x300dpi)		
	ADF: Single sided mono: 20ipm (300x600dpi) Single sided colour: 15ipm (300x600dpi)		
Colour Scanning Depth	24 bit/24 bit (input/output)		
	256 levels		
Greyscales			
Greyscales Compatibility	TWAIN , WIA, ICA		
-	TWAIN , WIA, ICA 216mm		
Compatibility			
Compatibility Maximum Scan Width	216mm		
Compatibility Maximum Scan Width Scan to E-mail	216mm TIFF/JPEG/PDF/Compact PDF		

FAX SPECIFICATIONS			
Modem Speed	33.6 Kbps (Up to 3 seconds/page) ⁴		
Receive Mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manu DRPD: Select Fax		
Fax Resolution	Normal: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi		
Fax Memory	Up to 256 pages ⁴		
Speed Dials	Up to 104 dials		
Group Dials/ Destinations	Max. 104 dials / Max. 50 destinations in one group		
Sequential Broadcast	Max. 114 destinations		
Memory Backup	Permanent fax memory backup (Backup with flash memory)		
Double Sided Faxing	Yes (Transmit and Receive)		
Other Features	Sender's Name (TTI), Direct Send, TX Report, Sequential Broadcasting		
	MEDIA HANDLING		
Scanner Type	Flatbed and Automatic Document Feeder (ADF)		
Paper Input (Standard)	250-sheet cassette 35-sheet ADF		
Paper Output	50-sheet		
Media Types	Plain paper, Recycled paper, Heavy Paper, Bond Paper, Label, Envelope		
Media Sizes	Cassette : A4, A5, A5 Landscape, B5, A6, Legal, Letter, Executiv Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, I6K, Envelop (COM10, DL, C5, Monarch), Custom sizes: Min. 76.0 x 127 mm Max. 216.0 x 356.0 mm		
	ADF: A4, A5, A6*, B5, B6, Legal, Letter, Custom sizes: Min. 105 x 148 mm Max 216 x 356 mm		
	*Attachement required		
Media Weights	Cassette: 60 to 163 g/m ² ADF: 105 to 128 g/m2 (Single sheet) 50 to 105 g/m ² (Multiple sheet)		
Double Sided Printing	Automatic A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, Foolscap 60 to 105 g/m2		



TECHNICAL **SPECIFICATIONS**

i-SENSYS MF287dw

INTERFACE & SOFTWARE			
Interface Type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX, Wireless 802.11b/g/n, Wireless Direct Connection		
Operating System Compatibility	Windows® 11 / Windows® 10 / Server® 2022 / Server® 2019 / Server® 2016 Mac OS X version 10.14 & up Linux ⁵		
Network Protocol	Print: TCP/IP (LPD/Port9100/IPP/IPPS/WSD) Scan: Push Scan: File: SMB3.0 (TCP/IP) E-mail/I-Fax: SMTP (send) Pull Scan: TCP/IP, USB Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security: TLS1.3, IP address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS) Security (wireless): IEEE802.1X Infrastructure Mode: WEP[64/128 bit), WPA-PSK(TKIP/AES), WPA2- PSK(TKIP/AES), WPA3-SAE (AES), WPA-EAP (AES), WPA2-EAP (AES), WPA3-EAP (AES)		
	Access Point Mode: WPA2-PSK(AES)		
Software and Printer Management	MF Scan Utility, Remote User Interface (RUI), Toner Status Tool		
GENERAL FEATURES			
Recommended Monthly Print Volume	250 - 2,500 pages per month		
Duty Cycle	Max. 50,000 pages per month ⁶		
Processor Speed	1200MHz		
Memory	256MB		
Control Panel	6-line LCD B&W Touch Screen		

Dimensions with Trays (W x D x H)	390 mm x 399 mm x 390 mm	
Installation Space (W x D x H)	435 mm x 620 mm x 812 mm	
Weight	Approx. 13.0 Kg	
Operating Environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)	
Power Source	220-240V(±10%) 50/60Hz (±2Hz)	
Power Consumption	Maximum: Approx. 1020 W Active printing: Approx. 410W Standby: Approx. 3.9 W Sleep mode: Approx. 0.6 W Typical Electricity Consumption (TEC): 0.27 kWh/ week* *As per US ENERGY STAR® version3.2 For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/ For_Work/Lot26/index.aspx	
Noise Levels	Sound Pressure ⁷ : Active: Simplex 53 dB / Duplex 52 dB Standby: Inaudible Sound Power ⁷ : Active: 70.0 dB or less Standby: N/A CONSUMABLES	
Contriduce		
Cartridges	Toner Cartridge 072 (1,400 pages ⁸) ⁹ Toner Cartridge 072H (4,100 pages ⁸) ⁹	

Footnotes:

- 1. A Canon PCL5e driver is not supplied, however PCL5e commands are supported

- A Canon PCLSe driver is not supplied, however PCL5e commands are supported on the device
 Scan by MF Scan Utility
 Scan by MF Scan Utility or Canon PRINT app
 Based on ITU-T Standard Chart No. 1
 Linux support both printing and scanning
 Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product
- 7. Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779
 8. Based on ISO/IEC 19752
- 9. Printer ships with Starter Cartridge (1000 pages)



i-SENSYS MF287dw

PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS MF287dw CB	6354C024AA	8714574688152
CONSUMABLES:		
PRODUCT NAME	Mercury Code	EAN Code
Toner Cartridge 072	5647C002AA	4549292228311

Canon (UK) Ltd

Canon Ireland

3006 Lake Drive

Citywest, Saggart

Co. Dublin, Ireland

canon.ie

Telephone No: 01 2052400

Facsimile No: 01 2052525

The Bower 4 Roundwood Avenue Stockley Park Uxbridge UB11 1AF Canon Inc. Canon.com

Canon Europe canon-europe.com

English Edition © Canon Europa N.V. 2024

