

IXUS 285 HS A STYLE AND PERFORMANCE IN YOUR POCKET



Fit style and performance in your pocket with this 12x zoom IXUS – share effortlessly via Wi-Fi and NFC.

25mm
WIDE
12x

12x optical zoom with ultra-wide angle

24x
ZoomPlus

Zoom to 24x with great quality

DIGIC
4+

Powerful DIGIC processing

7.5 cm
3.0"
LCD

7.5 cm (3.0") LCD

20.2 MEGA
PIXELS
HIGH-SENSITIVITY
CMOS

20.2 Megapixel CMOS



NFC simplifies
smartphone sharing



Canon



Pocketable style

This ultra-slim and stylish metal-bodied IXUS is easy to carry with you wherever you go and features a flexible 25mm ultra-wide 12x optical zoom lens with 24x ZoomPlus; so you can easily capture every moment, near or far, in superb quality photos and movies. Auto Zoom helps you select the best framing at the touch of a button.



Superb quality

Enjoy exceptional quality, detailed images even in low light thanks to a 20.2 Megapixels CMOS sensor and DIGIC 4+ processing. An intelligent optical Image Stabilizer ensures sharp stills and steady movies in any situation, while the large 7.5 cm (3.0") LCD screen allows easy shooting and playback.



Instant Full HD movies

Making great movies is fun and easy. With one touch of a button, you can effortlessly shoot great Full HD movies (1080p) in MP4 format. Experience the creative versatility of shooting movies using the optical zoom and still enjoy sharp, steady results thanks to the Dynamic Image Stabilizer.



Effortless creativity


At the touch of the shutter, Creative Shot automatically analyses the scene and creates 5 additional unique images of your original shot. Get close and capture stunning everyday detail with 1 cm Macro or simply point and shoot with Hybrid Auto and let the camera automatically create a fun HD (720p) movie summary of the day.




Quick connections

Connect to your compatible smart device with just one tap using Wi-Fi with Dynamic NFC for easy sharing. Use Image Sync to automatically back up new images to cloud services and capture great group shots with wireless Remote Shooting from your smart device. The Wi-Fi Button offers a quick and easy shortcut to Wi-Fi functions.


PRODUCT RANGE



PowerShot V1



PowerShot G7 X Mark III



PowerShot SX740 HS Lite Edition



IXUS 285 HS A

IMAGE SENSOR

Type	1/2.3 type back-illuminated CMOS
Effective Pixels	Approx. 20.2 M ^[8]
Effective / Total Pixels	Approx. 21.1 M
Colour Filter Type	Primary Colour

IMAGE PROCESSOR

Type	DIGIC 4+ with iSAPS technology
------	--------------------------------

LENS

Focal Length	4.5 – 54.0 mm (35 mm equivalent: 25 – 300 mm)
Zoom	Optical 12x ZoomPlus 24x Digital approx. 4x. (with Digital Tele-Converter Approx. 1.6x or 2.0x) Combined approx. 48x ^[1]

Maximum f/number

Construction	f/3.6 – f/7.0
Image Stabilisation	9 elements in 7 groups (1 double-sided aspherical UA lens, 1 double-sided aspherical lens, 1 single-sided aspherical lens) Yes (lens shift-type), approx. 2.5-stop ^[7] , Intelligent IS plus 4-axis Enhanced Dynamic IS

FOCUSING

Type	TTL
AF System/ Points	AiAF (Face Detection / 9-point), 1-point AF (fixed to centre)
AF Modes	Single, Continuous, Servo AF/AE ^[4] , Tracking AF
AF Point Selection	Size (Normal, Small)
AF Assist Beam	Yes
Closest Focusing Distance	1 cm (W) from front of lens in Macro

EXPOSURE CONTROL

Metering modes	Evaluative (linked to Face Detection AF frame), Centre-weighted average, Spot (Centre)
AE Lock	Yes
Exposure Compensation	+/- 2 EV in 1/3 stop increments. Enhanced i-Contrast for automatic dynamic range correction
ISO sensitivity	AUTO, 80, 100, 200, 400, 800, 1600, 3200

SHUTTER

Speed	1 – 1/2000 s (factory default) 15 – 1/2000 s (total range – varies by shooting mode)
-------	---

WHITE BALANCE

Type	TTL
Settings	Auto (including Face Detection WB), Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom.

COLOUR MATRIX

Type	sRGB
------	------

LCD MONITOR

Monitor	7.5 cm (3.0") LCD (TFT), Approx. 461,000 dots
Coverage	Approx. 100%
Brightness	Adjustable to one of five levels. Quick-bright LCD

FLASH

Modes	Auto, Manual Flash On / Off, Slow Synchro
Red-Eye Reduction	Yes
Flash Exposure Compensation	Face Detection FE, Smart Flash Exposure
Built-in Flash Range	50 cm – 4.0 m (W) / 1.0 m – 2.0 m (T)

SHOOTING

Modes	Hybrid Auto, Creative Shot, SCN (Smart Auto (32 scenes detected), P, Portrait, Smart Shutter (Smile, Wink Self-Timer, FaceSelf-Timer), High-speed Burst (5.0 MP), Handheld Night Scene, Low Light (5.0 MP), Fish-eye Effect, Miniature Effect, Toy Camera Effect, Monochrome, Super Vivid, Poster Effect, Fireworks, Long Shutter)
Modes in Movie	Smart Auto (21 scenes detected), P, Portrait, Miniature Effect, Monochrome, Super Vivid, Poster Effect, Fireworks
Photo Effects	My Colors (My Colors Off, Vivid, Neutral, Sepia, Black & White, Positive Film, Lighter Skin Tone, Darker Skin Tone, Vivid Blue, Vivid Green, Vivid Red, Custom Color)
Drive modes	Single, Continuous, Self-Timer
Continuous Shooting	Approx. 2.5 shots/s High-speed Burst (5.0 MP): Approx. 7.2 shots/s (all speeds are until memory card becomes full) ^{[2] [3]}

RECORDING PIXELS / COMPRESSION

Image Size	4:3 - (L) 5184 x 3888, (M) 2592 x 1944, (M1) 3648 x 2736, (M2) 2048 x 1536, (S) 640 x 480 16:9 - (L) 5184 x 2912, (M1) 3648 x 2048, (M2) 1920 x 1080, (S) 640 x 360 3:2 - (L) 5184 x 3456, (M1) 3648 x 2432, (M2) 2048 x 1368, (S) 640 x 424 1:1 - (L) 3888 x 3888, (M1) 2736 x 2736, (M2) 1536 x 1536, (S) 480 x 480
Compression	Resize option available in playback Superfine, Fine
Movies	(Full HD) 1920 x 1080, 29.97 fps, (HD) 1280 x 720, 29.97 fps, (L) 640 x 480, 29.97 fps

Movie Length

	Miniature Effect (HD, L) 6 fps, 3 fps, 1.5 fps Hybrid Auto (HD) 29.97 fps (Full HD & HD) Up to 4 GB or 29 min 59 s ^[5] (L) Up to 4 GB or 1 hour ^[3]
--	--

FILE TYPES

Still Image Type	JPEG compression, (Exif 2.3 [Exif Print] compliant) / Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant
Movies	MP4 [Video: MPEG4-AVC / H.264, Audio: MPEG4 AAC-LC (monaural)]

DIRECT PRINT

Canon Printers	Canon SELPHY Compact Photo Printers and Canon Inkjet Printers supporting PictBridge
PictBridge	Yes (via USB)

OTHER FEATURES

GPS	GPS via mobile (via Canon Camera Connect app with compatible smart devices) Yes, during shooting and playback Yes, with Auto Rotate
Red-Eye Correction	Yes, during playback
Intelligent Orientation Sensor	Approx. 2x – 10x
Histogram	Approx. 2, 10 s or Custom
Playback zoom	English, German, French, Dutch, Danish, Finnish, Italian, Greek, Norwegian, Portuguese, Russian, Swedish, Spanish, Ukrainian, Polish, Czech, Hungarian, Turkish, Simplified Chinese, Chinese (traditional), Japanese, Korean, Thai, Arabic, Romanian, Farsi, Hindi, Malay, Indonesian, Vietnamese, Hebrew
Self Timer	
Menu Languages	

INTERFACE

Computer	Hi-Speed USB composite connector (Mini-B compatible)
Other	HDMI Micro (Type-D) Connector A/V output, composite connector (PAL/NTSC)
Computer / Other	Wi-Fi (IEEE802.11b/g/n), (2.4 GHz only), with Dynamic NFC support ^[6]

MEMORY CARD

Type

microSD, microSDHC, microSDXC

SUPPORTED OPERATING SYSTEM

PC & Macintosh

Windows 10 / 8.1 / 8 / 7 SP1^[9]
Mac OS X 10.9 / 10.10 / 10.11

For Wi-Fi connection to a PC:
Windows 10 / 8.1 / 8 / 7 SP1
Mac OS X 10.9 / 10.10

SOFTWARE

Other

CameraWindow DC
Map Utility

Camera Connect app available on iOS and Android devices

POWER SOURCE

Batteries

Rechargeable Li-ion Battery NB-11L / NB-11LH
(NB-11LH battery and charger supplied)

Battery life

Approx. 180 shots

Eco Mode: Approx. 265 shots
Playback Mode: Approx. 240 min

ACCESSORIES

Cases / Straps

Soft Case DCC-1350
Soft Case DCC-1370

Power Supply & Battery Chargers

Battery Charger CB-2LFE
Rechargeable Li-ion Battery NB-11L / NB-11LH
Canon AV cable AVC-DC400
Interface Cable IFC-400PCU

PHYSICAL SPECIFICATIONS

Operating Environment

0 – 40 °C, 10 – 90 % humidity

Dimensions (W x H x D)

99.6 mm x 58.0 mm x 22.8 mm

Weight (incl. battery and card) *CIPA compliant*

146 g

Footnotes:

- ^[1] Depending on the image size selected.
- ^[2] Under conditions where the flash does not fire.
- ^[3] Depending on memory card speed / capacity / compression setting.
- ^[4] Some settings limit availability.
- ^[5] The following Speed Class memory cards are required for maximum record time:
(HD) 1280 x 720 Speed Class 4 or above. (Full HD) 1920 x 1080 Speed Class 6 or above.
(iFrame) 1280 x 720 Speed Class 6 or above.
- ^[6] Wi-Fi use may be restricted in certain countries or regions. Wi-Fi support varies by device and region.
- ^[7] Values at maximum optical focal length. Cameras whose focal length exceeds 350 mm (35 mm equivalent) are measured at 350 mm.
- ^[8] Image processing may cause a decrease in the number of pixels.
- ^[9] Software applications compatible with Windows 10 in Windows 10 Desktop Mode only

Disclaimers

- All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated.
- Subject to change without notice.

STYLE AND PERFORMANCE IN YOUR POCKET

IXUS 285 HS A

Fit style and performance in your pocket with this 12x zoom IXUS – share effortlessly via Wi-Fi and NFC.

Sales Start Date: September 2025 TBC



Product details

Product Name	Mercury Code	EAN Code
D.CAM IXUS 285 HS A BK EU26	7281C001AA	4549292250978
D.CAM IXUS 285 HS A BK SEE	7281C007AA	8714574693187
D.CAM IXUS 285 HS A SL EU26	7284C001AA	4549292251036
D.CAM IXUS 285 HS A SL SEE	7284C008AA	8714574693200

Optional accessories

Accessory Name	Mercury Code	EAN Code
Battery Pack NB-11LH	9391B001AB	4549292004472
Battery Charger CB-2LFE	8420B001BA	4960999977324
Interface Cable IFC-400PCU	9370A001AA	4960999209906
Audio-Video Cable AVC-DC400	2563B001AA	4960999570754
DCC-2400 Travel Case	1534C002AC	4549292072020

Measurement / logistic information

Product Name	Mercury Code	Pack type	Pack description	Quantity per pack	Length (cm)	Width (cm)	Height (cm)	Net weight (kg)	Gross Weight (kg)
D.CAM IXUS 285 HS A BK EU26 D.CAM IXUS 285 HS A BK SEE D.CAM IXUS 285 HS A SL EU26 D.CAM IXUS 285 HS A SL SEE	7281C001AA 7281C007AA 7284C001AA 7284C008AA	EA	Each	1	15.9	13.8	6	371.9	0.465
		CT	Carton	15	44.7	32.6	20.2	N/A	8.10
		EP	Euro Pallet	375	120	80	116	N/A	202
			Layers per Pallet	5					
			Cartons per Layer	5					
			Products per layer	75					

STYLE AND PERFORMANCE IN YOUR POCKET

IXUS 285 HS A

Fit style and performance in your pocket with this 12x zoom IXUS – share effortlessly via Wi-Fi and NFC.



What's in the box

IXUS 285 HS A

- Digital Camera IXUS 285 HS A
- Wrist Strap WS-800
- Battery Pack NB-11LH
- Battery Charger CB-2LFE
- AC Cable
- User Manual Kit

