COMPACT, SPEEDY A4 COLOUR MULTIFUNCTION PRINTERS FOR ESSENTIAL PRINTING AND SCANNING.

Create high quality documents with printers designed to fit seamlessly into a variety of work environments.

i-SENSYS MF660 Series



HIGH-QUALITY PRINTING

Produce high-quality output from toners with a wide range of colours and achieve bright, vibrant prints with excellent reproduction of both light and dark tones.

IMPROVE SUSTAINABILITY EFFORTS

Increase your sustainability efforts by opting for devices that increase use of recycled plastic. The light weight of printers also means fewer emissions during transport.

GREATER PRODUCTIVITY

Boost collaboration and productivity with fast print and scan speeds. Easily scan small-sized documents, including cheques and receipts, to cutdown on manual entry and paper storage.

SMOOTH USER EXPERIENCE

Use the intuitive UI to easily carry out a range of print and scan tasks and quickly reach relevant parts of the online manual via a QR code. Save time with the Master Setup which automatically downloads and installs software.

360-DEGREE SECURITY

A Security Settings Navigator recommends appropriate settings to protect against security leaks and cyber threats.

Canon

TECHNICAL SPECIFICATIONS

i-SENSYS MF660 Series

MAIN UNIT		
Machine type	Colour Laser All-In-One	
Available functions	Print, Copy, Scan and Fax	
	PRINTER	
Print speed	Single sided : Up to 25 ppm (A4) Up to 45.3 ppm(A5-Landscape) Double sided : Up to 15 ipm (A4)	
Printing method	Colour laser beam printing	
Print resolution	Up to 1200 x 1200 dpi	
Warm-up time	Approx. 13 seconds or less from power on	
First Print Out Time	Colour approx.: 10.93 seconds or less Mono approx.: 10.90 seconds or less	
Printer languages	i-SENSYS MF664Cdw : UFRII, PCL 5c², PCL6 i-SENSYS MF667Cdw : UFRII, PCL 5c², PCL6, Adobe® PostScript³	
Fonts	i-SENSYS MF664Cdw : 45 PCL fonts i-SENSYS MF667Cdw : 93 PCL fonts, 136 PostScript fonts	
Print margins	5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)	
Toner saver mode	Yes	
Advanced printing features	i-SENSYS MF664Cdw: Encrypted Secure Print Secure Print Print from USB memory key (JPEG/TIFF/PDF) Print from Cloud (Dropbox, GoogleDrive, OneDrive) (PDF/JPEG) Microsoft Universal Print support iOS: AirPrint, Canon PRINT app Android; Mopria certified, Canon Print Service Plug- in, Canon PRINT app, IPP everywhere i-SENSYS MF667Cdw: Encrypted Secure Print Secure Print Print from USB memory key (JPEG/TIFF/PDF) Print from Cloud (Dropbox, GoogleDrive, OneDrive) (PDF/JPEG) Microsoft Universal Print support Barcode Print ³ iOS: AirPrint, Canon PRINT app Android; Mopria certified, Canon Print Service Plug- in, Canon PRINT app, IPP everywhere	
Copy speed	Single sided (A4): Up to 25 ppm Double sided (A4): Up to 15 ipm	
First Copy Output Time (FCOT)	ADF (A4): Colour Approx. 10.6 seconds or less Mono Approx. 10.5 seconds or less Platen (A4): Colour Approx. 11.2 seconds or less Mono Approx. 11.0 seconds or less	
Copy resolution	Up to 600 x 600 dpi	
Copy modes	Text/Photo/Map (Default),Text/Photo/Map (quality), Printed Image, Text	
Double sided copying	2-sided to 2-sided (Automatic)	
Multiple copy	Up to 999 copies	
Reduction / Enlargement	25-400% in 1% increments	
Other features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Two-sided Original, Sort, N on 1, Sharpness, Erase Frame, Copy ID Card, Copy Passport, Color Mode, Reserved copy	

	SCANNER
Туре	Colour
Scan resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi
Scan speed	i-SENSYS MF664Cdw: Single sided mono: 50ipm (300x300dpi) Single sided colour: 40ipm (300x300dpi) Single sided colour: 20ipm (300x600dpi) Single sided colour: 20ipm (300x600dpi) i-SENSYS MF667Cdw: Single sided mono: 50ipm (300x300dpi) Single sided colour: 40ipm (300x300dpi) Double sided mono: 100ipm (300x300dpi) Double sided colour: 80ipm (300x300dpi) Single sided mono: 40ipm (300x600dpi) Single sided colour: 20ipm (300x600dpi) Double sided colour: 80ipm (300x600dpi) Double sided colour: 40ipm (300x600dpi)
Colour scanning depth	24 bit/24 bit (input/output)
Greyscales	256 levels
Compatibility	TWAIN , WIA, ICA
Max. scan width	216mm
Scan to E-mail	i-SENSYS MF664Cdw: TIFF/JPEG/PDF/Compact PDF/Searchable PDF / PDF/A-1b
Scan to PC	i-SENSYS MF667Cdw: TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF4/PDF (Digital signature)* / PDF/A-1b
Scan to Cloud ¹	TIFF/JPEG/PDF/PNG ⁵
iFAX	i-SENSYS MF667Cdw: ITU-T.37
FA	X (I-SENSYS MF667CDW ONLY)
Modem speed	33.6 Kbps (Up to 3 seconds/page ⁶)
Receive mode	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual
Fax resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi
	Ultra fine: 400 x 400 dpi
FAX memory	
FAX memory Speed dials	Ultra fine: 400 x 400 dpi
	Ultra fine: 400 x 400 dpi Up to 512 pages ⁶
Speed dials	Ultra fine: 400 x 400 dpi Up to 512 pages ⁶ Up to 281dials
Speed dials Group dials/destinations	Ultra fine: 400 x 400 dpi Up to 512 pages ⁶ Up to 281dials Max. 299 dials / Max. 299 destinations
Speed dials Group dials/destinations Sequential broadcast	Ultra fine: 400 x 400 dpi Up to 512 pages ⁶ Up to 281dials Max. 299 dials / Max. 299 destinations Max. 310 destinations Permanent fax memory backup (Backup with flash
Speed dials Group dials/destinations Sequential broadcast Memory backup	Ultra fine: 400 x 400 dpi Up to 512 pages ⁶ Up to 281dials Max. 299 dials / Max. 299 destinations Max. 310 destinations Permanent fax memory backup (Backup with flash memory)
Speed dials Group dials/destinations Sequential broadcast Memory backup Double sided faxing	Ultra fine: 400 x 400 dpi Up to 512 pages ⁶ Up to 281dials Max. 299 dials / Max. 299 destinations Max. 310 destinations Permanent fax memory backup (Backup with flash memory) Yes (Transmit and Receive) Sender's Name (TTI), Direct Send, Preview, TX Report,
Speed dials Group dials/destinations Sequential broadcast Memory backup Double sided faxing	Ultra fine: 400 x 400 dpi Up to 512 pages ⁶ Up to 281dials Max. 299 dials / Max. 299 destinations Max. 310 destinations Permanent fax memory backup (Backup with flash memory) Yes (Transmit and Receive) Sender's Name (TTI), Direct Send, Preview, TX Report, Sequential Broadcasting
Speed dials Group dials/destinations Sequential broadcast Memory backup Double sided faxing Other features	Ultra fine: 400 x 400 dpi Up to 512 pages ⁶ Up to 281dials Max. 299 dials / Max. 299 destinations Max. 310 destinations Permanent fax memory backup (Backup with flash memory) Yes (Transmit and Receive) Sender's Name (TTI), Direct Send, Preview, TX Report, Sequential Broadcasting MEDIA HANDLING i-SENSYS MF664Cdw: Platen, ADF i-SENSYS MF667Cdw: Platen, 2-sided ADF (single
Speed dials Group dials/destinations Sequential broadcast Memory backup Double sided faxing Other features Scanner type	Ultra fine: 400 x 400 dpi Up to 512 pages ⁶ Up to 281dials Max. 299 dials / Max. 299 destinations Max. 310 destinations Permanent fax memory backup (Backup with flash memory) Yes (Transmit and Receive) Sender's Name (TTI), Direct Send, Preview, TX Report, Sequential Broadcasting MEDIA HANDLING i-SENSYS MF664Cdw: Platen, ADF i-SENSYS MF667Cdw: Platen, 2-sided ADF (single pass) 250-sheet cassette 1-sheet manual feed slot



TECHNICAL SPECIFICATIONS

i-SENSYS MF660 Series

Media types	Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Label, Post card, Envelope
Media sizes	Cassette: A4, A5, A5 (Landscape), B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Indexcard, Envelop (COMIO, DL, C5, Monarch), Custom sizes: Min. 76.2 x 127 mm Max. 216 x 355.6 mm.
	Multi-purpose tray: A4, A5, A5 (Landscape), B5,A6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Indexcard, Envelope (COM10, DL, C5, Monarch), Custom sizes: Min 76.2 x 127 mm Max. 216 x 355.6 mm.
	ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 48 x 85.0 mm Max 216.0 x 355.6 mm
Media weights	Cassette: 60 to 163 g/m² (Up to 200 g/m² with Coated paper) Multi-purpose tray: 60 to 163 g/m² (Up to 200 g/m² with Coated paper) ADF: 50 to 105 g/m²
Double sided printing	Automatic Cassette: A4, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K Custom size - Min. 182 x 257 mm Max. 216.0 x 355.6 mm 60 to 200 g/m²
	INTERFACE & SOFTWARE
Interface type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection
Operating System compatibility	Windows® 11 / Windows® 10 / Server® 2025 /Server® 2022 / Server® 2019 / Server® 2016 Mac OS X version 10.15 & up Linux ⁷
Network Protocol	Print: TCP/IP (LPD/Port9100/IPP/IPPS/WSD) Scan: Push Scan: File: FTP (TCP/IP), SMB3.1.1 (TCP/IP) E-mail/I-Fax: SMTP (send), POP3 (receive) Pull Scan: TCP/IP Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security: TLS1.3, IPSec, IP address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS) Security (wireless): Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE (AES), WPA-EAP/AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE (AES)

Software and printer management	MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices Cooperating with External Security Audit System (Security Information and Event Management) eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Application Library
	GENERAL FEATURES
Processor Speed	1200MHz
Memory	1GB
Storage	4GB
Control panel	12.7 cm LCD Colour Touch Screen
Dimensions with trays (W x D x H)	451 mm x 460 mm x 413 mm
Installation space (W x D x H)	783 mm x 1,020 mm x 785 mm
Weight	Approx. 20.8 Kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Power Source	220-240V(±10%) 50/60Hz (±2Hz)
Power Consumption	Maximum: Approx. 980 W Active printing: Approx. 580W Standby: Approx. 12.0 W Sleep mode: Approx. 1.0 W Typical Electricity Consumption (TEC): 0.23 kWh/ week ¹¹ For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_ Work/Lot26/index.aspx
Noise Levels	Sound Pressure ⁸ : Active: Simplex 53 dB / Duplex 52 dB Standby: Inaudible Sound Power ⁸ : Active: Simplex 67 dB or less (BW) / 66 dB or less (CL) Duplex 66 dB or less Standby: Inaudible
	CONSUMABLES
Cartridges	Cartridge 075 Black (1,400 pages 9)10 Cartridge 075H Black (3,500 pages 9)10 Cartridge 075 Cyan (1,300 pages 9)10 Cartridge 075H Cyan (2,500 pages 9)10 Cartridge 075 Magenta (1,300 pages 9)10 Cartridge 075H Magenta (2,500 pages 9)10 Cartridge 075 Yellow (1,300 pages 9)10 Cartridge 075H Yellow (2,500 pages 9)10
	ACCESSORIES/ OPTIONS
Items	i-SENSYS MF667Cdw: TEL 6 Kit Long Cord (Telephone handset) Barcode Printing Kit-E1E Send PDF Security Feature Set-E1



TECHNICAL SPECIFICATIONS

i-SENSYS MF660 Series

- Notes:

 1. Subscription to a third party cloud service is required, and subject to their party terms and conditions.
- 2. Commands supported only. Third party driver or direct printing from application required. 3. Accessory Barcode Printing Kit-EIE is required
- 4. Accessory Send PDF Security Feature Set-E1 is required 5. Scan by MF Scan Utility or Canon PRINT
- 6. Based on ITU-T Standard Chart No. 1
- 7. Web distribution only. Linux support printing only. 8. Declared noise emission in accordance with ISO 7779.
- 9. Based on ISO/IEC 19798
- 10. Printer ships with Black: 700 pages, C/M/Y: 500 pages starter cartridges
- 11. As per US ENERGY STAR® version3.2.

Canon Inc. Canon.com

