



Mini GaN Charger 140W

with Display



140W of Power Across 4 Ports

Designed for versatility, this mini GaN wall charger delivers up to 140W total output across four ports, powering a laptop, tablet, and phones simultaneously.

A built-in TFT display shows real-time performance, while PPS technology optimizes fast, safe charging for each device. Advanced GaN technology ensures high efficiency, cooler operation, and a compact size.

Comprehensive protections guard against overcurrent, overvoltage, overheating, and short circuits, housed in a fireproof PC shell.

With interchangeable EU, UK, and US plugs, it's a compact, reliable travel charger for anywhere.



3x USB-C
PD 3.0



USB-A
QC 3.0



TFT
Display



Multi-Plug
Included

[verbatim.com](https://www.verbatim.com)



General Information

Approx. product dimensions LxWxH	71.5 x 36.5 x 71.5 mm
Product weight	340 g
Product material	Fireproof PC
Colour	Black
Input Plug Formats	US (Type A) / EU (Type C) / UK (Type G)
Supported devices	Laptop, iPhone, iPad, Smartphones, Tablet PCs, MP3/MP4 players, smartwatch, etc.
RoHS REACH	Yes
Certifications	CE/UKCA/FCC

Power

Input	100-240 V AC 50/60Hz 2.8A (Max)
Total Output	140W Max
Charging Mode	USB-C: PD 3.0 (PPS) USB-A: QC3.0, QC2.0

Single Port Output

USB-C1 Output PD 3.0 (PPS supported)	5V-11V/4.5A, 5V-21V/3A, 9V/3A, 15V/3A, 20V/5A, 28V/5A (Max:140W)
USB-C2 Output PD 3.0 (PPS supported)	5V-11V/4.5A, 5V-21V/3A, 9V/3A, 15V/3A, 20V/5A, 28V/5A (Max:140W)
USB-C3 Output PD 3.0 (PPS supported)	5V/3A, 9V/3A, 15V/2.65A, 20V/2A (Max:40W)
USB-A Output	5V/3A, 9V/2A, 12V/2.5A, (Max:30W)

Multiport Output	USB-C1 PD 3.0	USB-C2 PD 3.0	USB-C3 PD 3.0	USB-A QC 3.0
USB-C1+USB-C2	70W Max	70W Max	-	-
USB-C1+USB-C3	70W Max	-	40W Max	-
USB-C1+USB-A	100W Max	-	-	30W Max
USB-C2+USB-C3	-	100W Max	40W Max	-
USB-C2+USB-A	-	100W Max	-	30W Max
USB-C3+USB-A	-	-	24 W Max	
USB-C1+USB-C2+USB-C3	65W Max	45W Max	30W Max	-
USB-C1+USB-C2+USB-A	65W Max	45W Max	-	30W Max
USB-C1+USB-C3+USB-A	100W Max	-	24 W Max	
USB-C2+USB-C3+USB-A	-	100W Max	24 W Max	
USB-C1+USB-C2+USB-C3+USB-A	65W Max	45W Max	24 W Max	



US
Type A



UK
Type G



EU
Type C

Safety

Output short circuit protect	Yes
Over-voltage protection	Yes
Over-current protection	Yes
Over-temperature protection	Yes

Directives

Electromagnetic compatibility	2014/30/EC
Low voltage protection	2014/35/EC
General product safety	2001/95/EC
RoHS directive	2011/65/EC
Annex II	2015/863/EC
Test standards	EN 55032:2015+A11:2020+A1:2020 EN 55035:2017+A11:2020 EN 61000-3-2:2019+A2:2021 EN 61000-3-3:2013+A1:2019+A2:2021 EN IEC 62386-1:2020+A11:2020

Storage and Operating Conditions

Storage temperature	-25°C to +40°C
Operating temperature	0°C to +25°C
Operating Humidity	20% -80%

PN	Description	Tariff Code	Bar Code	EAN128 Code	EAN14 Code
30240	Verbatim Mini GaN Charger 140W with Display	85366990	23942302407	(02)00023942302407(37)06(91)864 (02)00023942302407(37)24(91)864	20023942302401 50023942302402

Logistic Information

Product Dimensions: L x W x H	71.5 x 36.5 x 71.5 mm
Product Weight:	340 g
Units per Pack:	1
Pack Dimensions:	110 x 55 x 129.5 mm
Pack Weight:	470.50 g
Packs per Inner Carton:	6
Inner Carton Dimensions: L x W x H	355 x 15 x 150 mm
Inner Carton Weight:	2983 g
Packs per Outer Carton:	24
Outer Carton Dimensions: L x W x H	375 x 275 x 325 mm
Outer Carton Weight:	12513 g
Outer Cartons per Layer:	12
Layers per Pallet:	4
Units per Pallet:	1152



Pack Contents

- Verbatim GaN Charger
- EU and UK plug Adapter
- Quick Start Guide



INDOOR USE ONLY.

Warranty

2 year limited warranty

For more information, please contact your key account manager

Publication date: 09/01/2026
© 2026 Verbatim. All rights reserved.
All brand names are registered trademarks of their respective owners.
Unauthorized use strictly prohibited.
Specifications are subject to change without prior notice.

