



Mini GaN Charger 65W

with Display



Compact Power with 65W and 3 Ports

Delivering up to 65W across three ports, this mini GaN wall charger powers a laptop, tablet, and smartphone at the same time.

The built-in TFT display shows real-time voltage, current, and output, giving clear insight into charging performance. PPS technology automatically adjusts power to each device for faster, safer charging.

Powered by advanced GaN technology, it offers high efficiency in a compact design, running cooler than traditional chargers. Comprehensive safety protections—including overcurrent, overvoltage, overheating, and short-circuit protection—are reinforced by a durable fireproof PC housing.

With interchangeable EU, UK, and US plugs, it's ideal for travel. Lightweight yet powerful, the Verbatim Mini GaN Charger with Display keeps your essential devices charged wherever you go.



2x USB-C
PD 3.0



USB-A
QC 3.0



TFT
Display



Multi-Plug
Included

[verbatim.com](https://www.verbatim.com)



General Information			
Approx. product dimensions LxWxH	58 x 31 x 58 mm		
Product weight	153 g		
Product material	Fireproof PC		
Colour	Black		
Input Plug Formats	US (Type A) / EU (Type C) / UK (Type G)		
Supported devices	Laptop, iPhone, iPad, Smartphones, Tablet PCs, MP3/MP4 players, smartwatch, etc.		
RoHS REACH	Yes		
Certifications	CE/UKCA/FCC		
Power			
Input	100-240 V AC 50/60Hz 1.8A (Max)		
Total Output	65W Max		
Charging Mode	USB-C: PD 3.0 (PPS) USB-A: QC3.0, QC2.0		
Single Port Output			
USB-C1 Output PD 3.0 (PPS supported)	5V-11V/4.5A, 5V-21V/5A, 5V/3A, 9V/3A, 15V/3A, 20V/3.25A (Max:65W)		
USB-C2 Output PD 3.0 (PPS supported)	5V-11V/4.5A, 5V-21V/5A, 5V/3A, 9V/3A, 15V/3A, 20V/3.25A (Max:65W)		
USB-A Output QC 3.0	5V/3A, 9V/2.22A, 12V/1.67A, (Max:20W)		
Multiport Output	USB-C1 PD 3.0	USB-C2 PD 3.0	USB-A QC 3.0
USB-C1+USB-C2	45W Max	20W Max	-
USB-C1+USB-A	45W Max	-	20W Max
USB-C2+USB-A	-	15W Max share	
USB-C1+USB-C2+USB-A	45W Max	15W Max share	



US
Type A



UK
Type G



EU
Type C



Safety

Output short circuit protect	Yes
Over-voltage protection	Yes
Over-current protection	Yes
Over-temperature protection	Yes

Directives

Electromagnetic compatibility	2014/30/EC
Low voltage protection	2014/35/EC
General product safety	2001/95/EC
RoHS directive	2011/65/EC
Annex II	2015/863/EC
Test standards	EN 55032:2015+A11:2020+A1:2020 EN 55035:2017+A11:2020 EN 61000-3-2:2019+A2021 EN 61000-3-3:2013+A1:2019+A2:2021 EN IEC 62386-1:2020+A11:2020

Storage and Operating Conditions

Storage temperature	-25°C to +40°C
Operating temperature	0°C to +25°C
Operating Humidity	20% -80%

PN	Description	Tariff Code	Bar Code	EAN128 Code	EAN14 Code
30238	Verbatim Mini GaN Charger 65W with Display	85366990	23942302384	(02)00023942302384(37)06(91)864 (02)00023942302384(37)24(91)864	20023942302388 50023942302389

Logistic Information

Product Dimensions: L x W x H	58 x 31 x 58 mm
Product Weight:	153 g
Units per Pack:	1
Pack Dimensions:	110 x 55 x 116 mm
Pack Weight:	277 g
Packs per Inner Carton:	6
Inner Carton Dimensions: L x W x H	355 x 125 x 140 mm
Inner Carton Weight:	1812 g
Packs per Outer Carton:	24
Outer Carton Dimensions: L x W x H	375 x 275 x 305 mm
Outer Carton Weight:	7809 g
Outer Cartons per Layer:	16
Layers per Pallet:	4
Units per Pallet:	1536



USB-C1 PD 3.0 (PPS) Max 65W

USB-C2 PD 3.0 (PPS) Max 65W

USB-A QC 3.0 Max 20W

Pack Contents

- Verbatim GaN Charger
- EU, US and UK plug Adapter
- Quick Start Guide



INDOOR USE ONLY.

Warranty

2 year limited warranty

For more information, please
contact your key account manager

Publication date: 09/01/2026
© 2026 Verbatim. All rights reserved.
All brand names are registered trademarks of their respective owners.
Unauthorized use strictly prohibited.
Specifications are subject to change without prior notice.

