SPEEDY, FEATURE-PACKED SINGLE-FUNCTION COLOUR PRINTERS, IDEAL FOR SMALL OFFICES

i-SENSYS LBP660 Series
Fast and highly productive colour single-function laser printing from feature-packed yet compact printers, perfect for small offices















Customisation

The Canon i-SENSYS LBP664Cx features an Application Library to further increase efficiency by automating and speeding up everyday tasks. Printing stored forms, templates and other basic documents can be undertaken with a single press of a button. The Application Library allows for the creation of a personalised screensaver in standby mode which can display important messages to users. Useful new application functions on the LBP660 series further boost productivity

Mobile connectivity

Small and medium sized business owners and staff on the go require mobile access to printing and scanning from any device. The Canon i-SENSYS LBP660 Series models ensure printing is only ever a tap away via a versatile range of mobile connection options including AirPrint (iOS) and Mopria (Android) support. There is also a range of tools and options to enhance mobile printing available from the Canon PRINT Business app

Faster print speeds

Time is crucial for small business owners, so Canon has ensured that its i-SENSYS LBP660 Series printers are ultra-quick with a lightning fast output of up to 27 single-sided A4 pages per minute. Regardless of the speed, there is no compromise on quality thanks to the printers' advanced engine – meaning a high-quality output every time

Intuitive touchscreen

Operation is simple. Canon i-SENSYS LBP664Cx boasts a 12.7cm LCD colour touch screen offering access to controls with a simple tap. Installation is easy and instantaneous, and the clear layout makes day-to-day control a breeze.



RANGE FEATURE STEP UP CHART





LBP663Cdw

LBP664Cx

A4 print speed	27ppm	27ppm
Secure PIN print	•	•
Automatic duplex printing	•	•
Display	5 line LCD	12.7cm colour touch screen
Universal Login Manager/uniFLOW Compatibility		•
Application Library		•

OPTION ACCESSORIES

Cassette Feeding Module-AF1

 Additional 550 sheet paper cassette, 1unit can be added to main unit.

Barcode Printing Kit-E1E (Available on LBP664Cx)

 Installs bar code fonts for bar code printing. This kit, which is delivered electronically, includes a license access certificate for activation.



TECHNICAL SPECIFICATIONS

i-SENSYS LBP660 Series

PRINTER ENGINE

Print speed

Single sided :

Single sided : Up to 27 ppm (A4) Up to 49 ppm(A5-Landscape) Double sided : Up to 24.5 ipm (A4)

Printing method Print resolution

Up to 600 x 600 dpi Up to 1200 x 1200 dpi

Print quality with Image Refinement Technology Warm-up time

First Page Out Time

Recommended Monthly Print Volume Duty cycle

Print margins

Advanced printing features

Colour laser beam printing

Approx. 13 seconds or less from power on

Colour approx.: 8.6 seconds or less Mono approx.: 7.7 seconds or less 750 - 4,000 pages per month

Max. 50,000 pages per month¹ 5 mm-top, bottom, left and right

LBP663Cdw:

Secure Print
Print from USB memory key (JPEG/TIFF/PDF)
Google Cloud Print Ready
IOS: AirPrint, Canon PRINT Business app
Android; Mopria certified, Canon Print Service Plug-in,
Canon PRINT Business app

LBP664Cx:
Secure Print
Print from USB memory key (JPEG/TIFF/PDF)
Barcode Print²
Touch & Print (NFC)
Google Cloud Print Ready
iOS: AirPrint, Canon PRINT Business app
Android; Mopria certified, Canon Print Service Plug-in,
Canon PRINT Business app

MEDIA HANDLING Paper input (Standard)

Paper input (Option)

Paper output Media types Media sizes

Media weights

250-sheet cassette 50-sheet multi-purpose tray

550-sheet cassette

150-sheet

Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Glossy paper, Label, Post card, Envelope

Cassette (Standard):
A4, A5, A5 (Landscape), B5, Legal, Letter, Executive,
Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR,
GLGL, Foolscap, 16K, Post card, Envelop (COMIO, DL, C5),
Custom sizes: Min. 100 x 148 mm Max. 216.0 x 355.6 mm.

Multi-purpose tray:
A4, A5, A5 (Landscape), B5, Legal, Letter, Executive,
Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR,
GLGL, Foolscap, 16K, Post card, Indexcard, Envelope
(COMIO, DL, C5, Monarch), Custom sizes: Min 76.2 x 127
mm Max. 216.0 x 355.6 mm.

Cassette (Optional):
A4, A5, B5, Legal, Letter, Executive, Statement, OFFICIO,
B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post
card, Envelop (COMIO, DL, C5), Custom sizes: Min. 100 x
148 mm Max. 216.0 x 355.6 mm.

Cassette (standard and ontional)

Cassette (standard and optional): 60 to 163 g/m² (Up to 200 g/m² with Glossy paper) Multi-purpose tray: 60 to 176 g/m² (Up to 200 g/m² with Glossy paper)

Double sided printing Automatic

Cassette (standard and optional):

A4, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K

Custom size - Min. 176 x 250 mm Max. 215.9 x 355.6 mm

60 to 200 g/m²

GENERAL FEATURES

Power requirements

Power consumption

220-240V (±10%) 50/60Hz (±2Hz)

Maximum: Approx. 1,380W or less Active printing: Approx. 470W

Standby: Approx. 17.0W or less

Sleep: Approx. 0.6W or less

Typical Electricity Consumption (TEC):

i-SENSYS LBP660 SERIES = 1.0 kWh/week8

For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx

Noise level

Active: Simplex 63 dB or less / Duplex 64 dB or less

Standby: 42 dB or less Sound pressure³

Active: Simplex 48 dB / Duplex 49 dB

Standby: 28 dB

LBP663Cdw: 437 mm x 469 mm x 313 mm

LBP664Cx: 476 mm x 469 mm x 379 mm LBP663Cdw: Approx. 20.7 kg

I BP664Cx: Approx 21.2 kg

Operating environment Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)

LBP663Cdw; 5 Line LCD, 3 LED (Job, Error, Energy saver),

Buttons, 10-key numeric keypad LBP664Cx: 12.7 cm LCD Colour Touch Screen

CONTROLLER

Dimensions (W x D x H)

Processor Speed

Memory

Printer Languages

Control panel

Fonts

Weight

Interface and connectivity

Software and Printer Management

800MHz x 2 1GB

UFRII, PCL5c4, PCL6, Adobe® PostScript

LBP663Cdw: 45 PCL fonts, 136 PS fonts LBP664Cx: 93 PCL fonts, 136 PS fonts

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection

Wheless Oct. 1971, Wheless Direct Confection
LBP663Cdw:
Remote User Interface (RUI),
Department ID Management,
Toner Status Tool,
iW Management Console: Server-based software for

centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.

Remote User Interface (RUI) Department ID Management,

Department ID Management,
Toner Status Tool,
IW Management Console: Server-based software for
centralised management of a fleet of devices
eMaintenance: embedded RDS allows remote
eMaintenance services such as meter capture, automatic emaintenance services such as meter capture, automatic consumables management and remote diagnostics. Universal Log-in Manager / uniFLOW online / uniFLOW online Express / uniFLOW compatibility Application Library

Operating Systems Compatibility Windows* 10 / Windows* 8.1 / Windows* 7 / Server* 2016 / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server*

Mac OS X version 10.9.5 & up / Mac OS 10.14 & up

CONSUMABLES Cartridge 055 Black (2.300 pages 6)7 All-in-One cartridges

> Cartridge 055 H Black (7,600 pages 6)7 Cartridge 055 Cyan (2,100 pages 6)7 Cartridge 055 H Cyan (5,900 pages 6)7

Cartridge 055 Magenta (2.100 pages 6) Cartridge 055 H Magenta (5,900 pages 6)7

Cartridge 055 Yellow (2,100 pages ⁶)⁷ Cartridge 055 H Yellow (5,900 pages 6)7

ACCESSORIES/OPTIONS

Items

CST.Feeding Module-AF1 (550-sheet cassette) Barcode Printing Kit-E1E

MiCard Attachment Kit-B1

Notes:

Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

Accessory - Barcode Printing Kit-EIE is required

Declared noise emission in accordance with ISO 9296

Commands supported only. Third party driver or direct printing from application required.

Web distribution only

Based on ISO/IEC 19752. Printer ships with starter cartridge (Black: 1.200, C/M/Y: 1.200 pages)

[8] As per US ENERGY STAR* version2.0.



SPEEDY, FEATURE-PACKED **SINGLE-FUNCTION COLOUR** PRINTERS, IDEAL FOR SMALL **OFFICES**

Fast and highly productive colour single-function laser printing from feature-packed yet compact printers, perfect for small offices



PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS LBP663Cdw	3103C017AA	8714574662282
i-SENSYS LBP664Cx	3103C015AA	8714574662268

ACCESSORIES:

PRODUCT NAME	Mercury Code	EAN Code
Cassette Feeding Module-AF1	0732A032AA	4549292077278
MiCard Attachment kit-B1	5146B002AA	4549292027235
Barcode Printing Kit-E1E	5143B002AA	N/A (e-delivery)

CONSUMABLES:

PRODUCT NAME	Mercury Code	EAN Code
Cartridge 055 Black	3016C002AA	4549292124699
Cartridge 055 H Black	3020C002AA	4549292124842
Cartridge 055 Yellow	3013C002AA	4549292124606
Cartridge 055 H Yellow	3017C002AA	4549292124729
Cartridge 055 Magenta	3014C002AA	4549292124637
Cartridge 055 H Magenta	3018C002AA	4549292124767
Cartridge 055 Cyan	3015C002AA	4549292124668
Cartridge 055 H Cyan	3019C002AA	4549292124804

Canon Ireland 3006 Lake Drive Citywest, Saggart Co. Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525

canon.ie

Canon (UK) Ltd

Woodhatch Reigate Surrey RH2 8BF Telephone No: 01737 220000

Facsimile No: 01737 220022 canon.co.uk

canon.com Canon Europe

Canon Inc.

canon-europe.com **English** edition © Canon Europa N.V.,2019

